



Type DT93-AHS & DT93-AHD
STAINLESS STEEL FLOOR ACCESS DOORS
FOR DIRECT TRAFFIC APPLICATIONS UP TO
ASTM C1802-14 LOAD LEVEL 7

TABLE OF CONTENTS

Vendor Data
Material Data Sheet
Specification
Component Parts List
Storage, Handling, Installation & Maintenance Instructions
Limited Warranty

VENDOR DATA

USF FABRICATION

3200 W. 84 ST.

HIALEAH, FL 33018

PH: 305.364.8200

TOLL FREE: 800.258.6873

FAX: 305.882.1577

EMAIL: SERVICE@USFFAB.COM

WEBSITE: WWW.USFFAB.COM

CONTACT: LEAH STENBERG

Type DT93-AHS & DT93-AHD
STAINLESS STEEL FLOOR ACCESS DOORS
FOR DIRECT TRAFFIC APPLICATIONS UP TO
ASTM C1802-14 LOAD LEVEL 7

MATERIAL DATA SHEET

1. Door leaf shall be 3/8 -in. thick Stainless Steel diamond pattern plate, reinforced with Stainless Steel channels to achieve an ASTM C1802-14 LOAD LEVEL 7 wheel load rating.
2. Frame members shall be minimum 1/2 -in. thick Stainless Steel.
3. The following items shall be Type 316 Stainless Steel: hinges, hold-open arm, and all attaching hardware.
4. Units shall carry a Five (5) Year Guarantee against defects in material and/or workmanship.

Type DT93-AHS & DT93-AHD
STAINLESS STEEL FLOOR ACCESS DOORS
FOR DIRECT TRAFFIC APPLICATIONS UP TO
ASTM C1802-14 LOAD LEVEL 7

STANDARD FEATURES:

- 316 Stainless Steel hold-open arms with secondary latch mechanism/release handle
- 316 Stainless Steel hinges and tamper resistant attaching hardware
- Stainless Steel lift handle
- Stainless Steel open compression springs
- Recessed padlock box bolted for traffic
- Single or double leaf construction bolted for traffic
- ASTM C1802-14 LOAD LEVEL 7 wheel load rating
- 5 Year warranty against defects in material and workmanship

Type DT93-AHS & DT93-AHD
STAINLESS STEEL FLOOR ACCESS DOORS
FOR DIRECT TRAFFIC APPLICATIONS UP TO
ASTM C1802-14 LOAD LEVEL 7

SPECIFICATION

The floor access door shall be Model DT93-AHS (single leaf) or DT93-AHD (double leaf) as manufactured by U.S.F. Fabrication, Inc. with the size being specified on the plans.

Door leaf(s) shall be 3/8-inch thick Stainless Steel diamond plate reinforced for AASHTO HL93 wheel loads and designed for roadways that may receive up to ASTM C1802-14 load level 7 wheel loads up to 70 mph. Covers shall be bolted to the frame.

The frame shall be minimum ½ " thick Stainless Steel with anchors and door seat on all four sides and must include a skirt so that the overall height of the frame is a minimum of 12"

The floor access door shall be equipped with a flush lifting handle that does not protrude above the cover, and a 316 Stainless Steel hold open arm with a secondary latching mechanism/release handle that secures the cover in its full upright, open position.

The door shall have 316 Stainless Steel hinges with 316 Stainless Steel tamper resistant bolts/locknuts.

The door shall be equipped with a bolted cover with a bolted recessed padlock box

The door shall have Stainless Steel lift assist to assist in opening the cover and reduce the force during closing.

Installation shall be in accordance with the manufacturer's attached instructions. The door shall be manufactured and assembled in the United States.

Manufacturer shall guarantee the door against defects in materials and workmanship for a period of five (5) years.

Type DT93-AHS & DT93-AHD
STAINLESS STEEL FLOOR ACCESS DOORS
FOR DIRECT TRAFFIC APPLICATIONS UP TO
ASTM C1802-14 LOAD LEVEL 7

STORAGE, HANDLING, INSTALLATION and MAINTENANCE

STORAGE:

Prior to installation floor access doors should be stored in a dry area that is free of dirt and debris. Floor access doors should be stored on the original shipping pallets.

HANDLING:

Standard practice precautions should be taken whenever handling or moving palletized floor access doors by forklift.

INSTALLATION:

For proper installation, U.S.F. Fabrication, Inc. recommends the following:

1. Form work must be flush to the inside of frame.
2. Secure unit to formwork using standard construction practices.
3. When pouring concrete, cover should be in the closed position.
4. Concrete to finish flush with top of unit framework.
5. Unit shall be left in framework for not less than 24 hours.
6. Clean all excess concrete from frame, cover seat; and in the case of a trough type frame, the drainage coupling.

MAINTENANCE:

Since all components of the floor access doors manufactured by U.S.F. Fabrication, Inc. are manufactured of aluminum, Stainless Steel or Stainless Steel, they require minimal maintenance. For optimum product life the manufacturer recommends the following procedures be performed annually:

1. Apply graphite to the interior of all locking devices.
2. Apply a light coating of machine oil to all hinges and hardware.
3. Remove all debris from the cover seat and around hinges.
4. Check and tighten any loose hardware.
5. In the case of a trough frame model, remove loose debris from the trough.
6. Cover bolts require Loktite 241 Blue (or equivalent) and the cover to be torqued to the force listed on recessed padlock box plate.



Limited Warranty

U.S.F. Fabrication, Inc., hereafter called the "Company," extends the following limited warranty to Buyer hereafter referred to as "Customer".

The commencement date of this warranty is the date of first purchase by Customer from the Company of the complained of Product and extends for the noted period depending on the Product purchased as follows:

Steel hatches and access doors: 5 years.

Aluminum hatches and access doors: 10 years.

All other products and miscellaneous fabrication items: 1 year

1. Coverage

The Company expressly warrants to the Customer that the product purchased from Company ("Product") will be free from defects in materials and workmanship. Any implied warranties, to the extent they exist and are legally enforceable, for merchantability, workmanship, or fitness for intended use on any Product shall terminate on the same date as the above stated express warranty commences. This warranty gives you specific legal rights, and you may have other rights that vary from state to state.

2. Company's Obligations

If a covered defect occurs during the warranty period, the Company agrees to replace or pay the Customer the reasonable cost of replacing the defective item. The Company's total liability under this warranty is limited to the purchase price of the Product. The choice among replacement or payment is the Company's. Any steps taken by the Company to correct defects shall not act to extend the term of this warranty. The Company shall pay standard freight charges for warranty components.

3. Customer's Obligation

The Company must be notified in writing by the Customer of the existence of any defect before the Company is responsible for the correction of that defect. Written notice of a defect must be received by the Company prior to the expiration of the warranty on that Product and no action at law or in equity may be brought by the Customer against the Company for failure to remedy or repair any defect about which the Company has not received timely notice in writing. The Customer must provide the Company with access to the defective Product during the Company's normal business hours and Customer may not commence any repair without first obtaining Company's written consent. Customer shall indemnify and hold Company and its affiliates, divisions, officers, owners, employees and agents harmless from any and all claims, actions, costs, losses, damages, liabilities, penalties and other expenses, including reasonably attorney's fees and costs, resulting from death, bodily injury, property damage or other claims, including those of third parties, relating to or arising from the Customer's negligence, actions or inactions with respect to the Product sold by Company or any failure of Customer to install, service or maintain the Product in accordance with stated specifications and in a commercially reasonable fashion.

4. Exclusions

The following items are excluded from this limited warranty:

- a. Defects in any item that was not part of the original Product as supplied by the Company.
- b. Any defect caused by or worsened by negligence, improper maintenance, lack of maintenance, tampering, accident, abuse, misapplication, improper action or inaction, or willful or malicious acts by any party other than the Company, its employees, agents, or trade contractors.
- c. Normal wear and tear.
- d. Loss or damage caused by acts of God, including but not limited to fire, explosion, smoke, water, and circumstances that are not reasonably foreseeable.
- e. Any defect or damage caused by nuisance, as well as careless or negligent transport.
- f. Any damage to the extent it is caused or made worse by the failure of anyone other than the Company or its employees, agents, or trade contractors to comply with the requirements of this warranty.
- g. Failure of Customer to take timely action to minimize loss or damage or failure of Customer to give the Company timely notice of the defect.
- h. Insect, animal or storage damage.
- i. Special, incidental, consequential, punitive or business loss damages.

5. Exclusive Warranty

THIS WARRANTY IS LIMITED, NON-TRANSFERABLE AND CUSTOMER'S SOLE AND EXCLUSIVE WARRANTY REGARDING THE PRODUCT AND IS IN LIEU OF ANY OTHER WARRANTY, WHETHER EXPRESS OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ANY OTHER WARRANTY OF QUALITY. ALL WARRANTIES OTHER THAN THIS LIMITED WARRANTY (INCLUDING ALL IMPLIED WARRANTIES LISTED IN THE PREVIOUS SENTENCE) ARE EXPRESSLY EXCLUDED AND DISCLAIMED. TO THE EXTENT LOCAL LAW PROVIDES THAT ANY IMPLIED WARRANTIES MAY NOT BE EXCLUDED OR DISCLAIMED, THOSE WARRANTIES ARE LIMITED IN DURATION TO THE SHORTER OF (i) THE DURATION OF THE EXPRESS WARRANTY PROVIDED IN THIS LIMITED WARRANTY OR (ii) THE SHORTEST DURATION REQUIRED BY LOCAL LAW. COMPANY'S TOTAL LIABILITY FOR ALL CLAIMS OF ANY KIND WILL NOT EXCEED THE PURCHASE PRICE PAID TO COMPANY FOR THE PRODUCT IN QUESTION.

6. Dispute Resolution

The Customer shall promptly contact the Company's warranty department regarding any claims and both Customer and Company shall agree on a day and time to discuss the issue. If discussions between the parties do not resolve such matter, either party may, upon written notice to the other party, submit the issue to mediation before a jointly selected certified and neutral mediator at a location mutually agreed upon by the parties. The expenses of the mediator shall be shared equally by Company and Customer but each party shall bear its own legal fees and costs. If the mediator declares an impasse, then the parties shall seek resolution of the matter through a court of competent jurisdiction within Miami-Dade County, Florida, with the prevailing party in any such action being entitled to recover its reasonable attorney's fees and costs from the other party.

USF FABRICATION - 3200 W. 84 ST. - HIALEAH, FL 33018

PH: 305.364.8200 TOLL FREE: 800.258.6873 FAX: 305.882.1577

EMAIL: SERVICE@USFFAB.COM