



- NOTES:
- 1- MATL: STEEL, PAINTED TO FLA. DOT SPECIFICATIONS.
  - 2- LOADING: DESIGNED FOR OFF STREET LOCATIONS WHICH MAY OCCASIONALLY RECEIVE H-20 WHEEL LOADS.
  - 3- APPROX. WEIGHT 391 LBS.

REV.	DATE	BY	APP'D	DESCRIPTION
2	02/17/20	PR	PR	WELDING WAS CHANGED TO MEET PEDESTRIAN STANDARDS
1	02/2/16	C.S.	C.S.	ADJUSTED TOLERANCES, UPDATED TITLE BLOCK

THIS DOCUMENT IS THE PROPERTY OF U.S.F. FABRICATION, INC AND CONTAINS PROPRIETARY INFORMATION. IT SHALL NOT BE MODIFIED, COPIED, FURNISHED NOR DISTRIBUTED (IN WHOLE OR IN PART) WITHOUT PROPER AUTHORIZATION OF U.S.F. FABRICATION, INC.

INTERPRET DIMENSIONS AND TOLERANCES PER ASME Y14.5M
BREAK ALL SHARP CORNERS & EDGES TO 0.01
TOLERANCES UNLESS OTHERWISE SPECIFIED FRACTIONAL
INCHES = ± 1/16
1/16 = ± 1/32
1/32 = ± 1/64

COPYRIGHT © 2016  
ALL RIGHTS RESERVED

GRATE RVT 6646 H20 PTD			
DWN. BY: JM/ALJ	SCALE: 1"=1"	SHEET: 1 of 1	DATE: 7/28/15
CHK. BY: JM/ALJ	DWG.# 1000001490	SHEET SIZE: B	REV: 2