



NOTES:

- 1- MATL: STEEL, PAINTED TO FLA. DOT SPECS
- 2- LOADING: DESIGNED FOR OFF STREET LOCATIONS WHICH MAY OCCASIONALLY RECEIVE H-20 WHEEL LOADS.
- 3- APPROX. WEIGHT: 826 LBS

REV.	DATE	BY	APP'D	DESCRIPTION
4	08/14/20	ALJ	ALJ	UPDATED PER ECN 20-056: CHANGED NOTCH TO BE 6 1/4"
3	02/17/20	PR	PR	WELDING WAS CHANGED TO MEET PEDESTRIAN STANDARDS
2	10/3/19	C.S.	C.S.	INDEX 425-053 WAS INDEX 233
1	02/3/16	C.S.	C.S.	ADJUSTED TOLERANCES, UPDATED TITLE BLOCK

THIS DOCUMENT IS THE PROPERTY OF U.S.F. FABRICATION, INC AND CONTAINS PROPRIETARY INFORMATION. IT SHALL NOT BE MODIFIED, COPIED, FURNISHED NOR DISTRIBUTED (IN WHOLE OR IN PART) WITHOUT PROPER AUTHORIZATION OF U.S.F. FABRICATION, INC.

INTERPRET DIMENSIONS AND TOLERANCES PER ASME Y14.5M  
 BREAK ALL SHARP CORNERS & EDGES TO 0.01  
 TOLERANCES UNLESS OTHERWISE SPECIFIED FRACTIONAL  
 INCHES = ± 1/16  
 1/16 = ± 1/32  
 1/32 = ± 1/64

COPYRIGHT © 2020  
 ALL RIGHTS RESERVED

FLA. D.O.T. INDEX 425-053  
 TYPE "G" DITCH BOTTOM INLET



**U.S.F. FABRICATION INC.**  
 HIALEAH, FLORIDA

GRATE RVT 6661 H20 PTD

DWN. BY: DAV/ALJ	SCALE: 1/16" = 1"	SHEET: 1 of 1	DATE: 7/30/15
CHK. BY: DAV/ALJ	DWG.# 100001499	SHEET SIZE: B	REV: 4