



- NOTES:
- 1- MATL: STEEL A-36, PAINTED TO FLA. DOT SPECIFICATIONS.
 - 2- LOADING: DESIGNED FOR OFF STREET LOCATIONS WHICH MAY OCCASIONALLY RECEIVE H-20 WHEEL LOADS
 - 3- APPROX. WEIGHT: 411 LBS.

REV.	DATE	BY	APP'D	DESCRIPTION
2	02/17/20	PR	PR	WELDING WAS CHANGED TO MEET PEDESTRIAN STANDARDS
1	02/3/16	C.S.	C.S.	ADJUSTED TOLERANCES, UPDATED TITLE BLOCK

THIS DOCUMENT IS THE PROPERTY OF U.S.F. FABRICATION, INC AND CONTAINS PROPRIETARY INFORMATION. IT SHALL NOT BE MODIFIED, COPIED, FURNISHED NOR DISTRIBUTED (IN WHOLE OR IN PART) WITHOUT PROPER AUTHORIZATION OF U.S.F. FABRICATION, INC.

INTERPRET DIMENSIONS AND TOLERANCES PER ASME Y14.5M
BREAK ALL SHARP CORNERS & EDGES TO 0.01
TOLERANCES UNLESS OTHERWISE SPECIFIED FRACTIONAL
INCHES = ± 1/16
1/16 = ± 1/32
1/32 = ± 1/64

COPYRIGHT © 2016
ALL RIGHTS RESERVED



U.S.F. FABRICATION INC.
HIALEAH, FLORIDA

GRATE RVT 6681 H20 PTD

DWN. BY: JM/ALJ	SCALE: 1"=12"	SHEET: 1 of 1	DATE: 7/30/15
CHK. BY: JM/ALJ	DWG.# 100001507	SHEET SIZE: B	REV: 2