



**NOTE:**

- 1-MATERIAL: STEEL, PAINTED TO FLA. DOT SPECIFICATION.
- 2-LOADING: DESIGNED FOR OFF STREET LOCATIONS WHICH MAY OCCASIONALLY RECEIVE H-20 WHEEL LOADS.
- 3-APPROX. WEIGHT: 235 LBS.
- 4-APPROX. OPEN AREA: 460 SQ. IN.

REV.	DATE	BY	APP'D	DESCRIPTION
1	02/2/16	C.S.	C.S.	ADJUSTED TOLERANCES, UPDATED TITLE BLOCK

THIS DOCUMENT IS THE PROPERTY OF U.S.F. FABRICATION, INC AND CONTAINS PROPRIETARY INFORMATION. IT SHALL NOT BE MODIFIED, COPIED, FURNISHED NOR DISTRIBUTED (IN WHOLE OR IN PART) WITHOUT PROPER AUTHORIZATION OF U.S.F. FABRICATION, INC.

INTERPRET DIMENSIONS AND TOLERANCES PER ASME Y14.5M  
BREAK ALL SHARP CORNERS & EDGES TO 0.01

TOLERANCES UNLESS OTHERWISE SPECIFIED FRACTIONAL

INCHES = ± 1/16  
1/16 = ± 1/32  
1/32 = ± 1/64

COPYRIGHT © 2016  
ALL RIGHTS RESERVED



**U.S.F. FABRICATION INC.**  
HIALEAH, FLORIDA

GRATE PLUG WELD 6641 H20 PTD

OWN. BY: MJH/ALJ	SCALE: 1"=12"	SHEET: 1 of 1	DATE: 7/28/15
CHK. BY: ECS/ALJ	DWG.# 1000001514	SHEET SIZE: B	REV: 1