



- NOTES:
- 1- MATL: STEEL, PAINTED TO F.D.O.T SPECIFICATIONS.
  - 2- LOADING: DESIGNED FOR OFF STREET LOCATIONS WHICH MAY OCCASIONALLY RECEIVE H-20 WHEEL LOADS.
  - 3- APPROX. WEIGHT: 375 LBS.

REV.	DATE	BY	APP'D	DESCRIPTION
5	09/25/20	ALJ	ALJ	PER ECN 20-056: REMOVED CURVED NOTCH
4	08/14/20	ALJ	ALJ	UPDATED PER ECN 20-056: CHANGED NOTCH TO BE 6 1/4"
3	07/20/20	ALJ	ALJ	WELDING WAS UPDATED TO MEET FLDOT STANDARDS PER NCR 4543
2	02/17/20	PR	PR	WELDING WAS CHANGED TO MEET PEDESTRIAN STANDARDS
1	02/2/16	C.S.	C.S.	ADJUSTED TOLERANCES, UPDATED TITLE BLOCK

THIS DOCUMENT IS THE PROPERTY OF U.S.F. FABRICATION, INC AND CONTAINS PROPRIETARY INFORMATION. IT SHALL NOT BE MODIFIED, COPIED, FURNISHED NOR DISTRIBUTED (IN WHOLE OR IN PART) WITHOUT PROPER AUTHORIZATION OF U.S.F. FABRICATION, INC.

INTERPRET DIMENSIONS AND TOLERANCES PER ASME Y14.5M  
BREAK ALL SHARP CORNERS & EDGES TO 0.01

TOLERANCES UNLESS OTHERWISE SPECIFIED FRACTIONAL

INCHES = ± 1/16  
1/16 = ± 1/32  
1/32 = ± 1/64

COPYRIGHT © 2020  
ALL RIGHTS RESERVED



**U.S.F. FABRICATION INC.**  
HIALEAH, FLORIDA

GRATE RVT 6632 H20 PTD

DWN. BY: ALJ	SCALE: 1"=1'	SHEET: 1 of 1	DATE: 7/28/15
CHK. BY: ALJ	DWG.# 100001522	SHEET SIZE: B	REV: 5