



LOUISIANA TYPE-C

NOTES:

- MATL: STEEL A36, PAINTED WITH ONE COAT OF SHOP PRIMER.
- LOADING: DESIGNED FOR OFF STREET LOCATIONS WHICH MAY OCCASIONALLY RECEIVE H-20 WHEEL LOADS.
- APPROX. GRATE WEIGHT: 250.94 LBS. ±5%
- ALL JOINTS FULL DEPTH 1/4" FILLET WELDS WITH SEAL WELDS TOP AND BOTTOM UNLESS NOTED OTHERWISE.

REV.	DATE	BY	APP'D	DESCRIPTION
5	07/20/20	ALJ	ALJ	UPDATED WELDING TO MATCH LADOT STANDARDS PER NCR 4539
4	04/22/20	LE	LE	UPDATED WELDING TO MATCH N.Y. D.O.T. STANDARDS PER NCR 4472
3	02/17/20	PR	PR	WELDING WAS CHANGED TO MEET PEDESTRIAN STANDARDS
2	01/31/18	C.S.	C.S.	UPDATED GRATE BASED ON NEW DOT CHANGES
1	02/3/16	C.S.	C.S.	ADJUSTED TOLERANCES, UPDATED TITLE BLOCK

THIS DOCUMENT IS THE PROPERTY OF U.S.F. FABRICATION, INC AND CONTAINS PROPRIETARY INFORMATION. IT SHALL NOT BE MODIFIED, COPIED, FURNISHED NOR DISTRIBUTED (IN WHOLE OR IN PART) WITHOUT PROPER AUTHORIZATION OF U.S.F. FABRICATION, INC.

INTERPRET DIMENSIONS AND TOLERANCES PER ASME Y14.5M  
BREAK ALL SHARP CORNERS & EDGES TO 0.01

TOLERANCES UNLESS OTHERWISE SPECIFIED FRACTIONAL  
INCHES = ± 1/16  
1/16 = ± 1/32  
1/32 = ± 1/64

COPYRIGHT © 2020 ALL RIGHTS RESERVED

 U.S.F. FABRICATION INC.  
HIALEAH, FLORIDA

GRATE RVT 6673 H20 PTD

OWN. BY: ALJ	SCALE: 1=12	SHEET: 1 of 1	DATE: 8/3/15
CHK. BY: ALJ	DWG.# 100001533	SHEET SIZE: B	REV: 8

REV.	DATE	BY	APP'D	DESCRIPTION
8	07/26/22	CT	CT	MOVED STAMP TO LOWER END OF SECOND TO LAST BEARING BAR
7	07/24/20	ALJ	ALJ	ADDED SEAL WELDS TO BEARING BARS
6	07/22/20	ALJ	ALJ	CORRECTED WELDING FOR BEARING BARS