



MOD. "D" INLET TRAFFIC

- NOTES:**
- 1- ADD 3/8" TO LENGTH OF GRATE FOR RIVETS.
  - 2- MATL: STEEL A-36, PAINTED TO FLA DOT SPECIFICATIONS.
  - 3- LOADING: DESIGNED FOR OFF STREET LOCATIONS. WHICH MAY OCCASIONALLY RECEIVE H-20 WHEEL LOADS.

| REV. | DATE     | BY   | APP'D | DESCRIPTION  |
|------|----------|------|-------|--|
| 5    | 09/25/20 | ALJ  | ALJ   | PER ECN 20-056: REMOVED CURVED NOTCH               |
| 4    | 8/14/20  | ALJ  | ALJ   | UPDATED PER ECN 20-056: CHANGED NOTCH TO BE 6 1/4" |
| 3    | 07/22/20 | ALJ  | ALJ   | UPDATED BANDING WELDS PER NCR 4460                 |
| 2    | 02/17/20 | PR   | PR    | WELDING WAS CHANGED TO MEET PEDESTRIAN STANDARDS   |
| 1    | 02/3/16  | C.S. | C.S.  | ADJUSTED TOLERANCES, UPDATED TITLE BLOCK           |

THIS DOCUMENT IS THE PROPERTY OF U.S.F. FABRICATION, INC AND CONTAINS PROPRIETARY INFORMATION. IT SHALL NOT BE MODIFIED, COPIED, FURNISHED NOR DISTRIBUTED (IN WHOLE OR IN PART) WITHOUT PROPER AUTHORIZATION OF U.S.F. FABRICATION, INC.

INTERPRET DIMENSIONS AND TOLERANCES PER ASME Y14.5M  
 BREAK ALL SHARP CORNERS & EDGES TO 0.01  
 TOLERANCES UNLESS OTHERWISE SPECIFIED FRACTIONAL  
 INCHES = ± 1/16  
 1/16 = ± 1/32  
 1/32 = ± 1/64

COPYRIGHT © 2020  
 ALL RIGHTS RESERVED



**U.S.F. FABRICATION INC.**  
 HIALEAH, FLORIDA

GRATE RVT 6694 H20 PTD

|              |                 |               |               |
|--------------|-----------------|---------------|---------------|
| OWN. BY: ALJ | SCALE: 1"=12"   | SHEET: 1 of 1 | DATE: 7/30/15 |
| CHK. BY: ALJ | DWG.# 100001537 | SHEET SIZE: B | REV: 5        |