



NOTES:

- 1- ADD $\frac{3}{8}$ IN TO LENGTH OF GRATE FOR RIVETS.
- 2- MATL: STEEL A-36, PAINTED TO FLA DOT SPECIFICATIONS.
- 3- LOADING: DESIGNED FOR OFF STREET LOCATIONS WHICH MAY OCCASIONALLY RECEIVE H-20 WHEEL LOADS.

REV.	DATE	BY	APP'D	DESCRIPTION
5	09/25/20	ALJ	ALJ	PER ECN 20-056: REMOVED CURVED NOTCH
4	08/14/20	ALJ	ALJ	UPDATED PER ECN 20-056: CHANGED NOTCH TO BE 6 1/4"
3	07/22/20	ALJ	ALJ	UPDATED BANDING WELDS PER NCR 4460
2	02/17/20	PR	PR	WELDING WAS CHANGED TO MEET PEDESTRIAN STANDARDS
1	02/3/16	C.S.	C.S.	ADJUSTED TOLERANCES, UPDATED TITLE BLOCK

THIS DOCUMENT IS THE PROPERTY OF U.S.F. FABRICATION, INC AND CONTAINS PROPRIETARY INFORMATION. IT SHALL NOT BE MODIFIED, COPIED, FURNISHED NOR DISTRIBUTED (IN WHOLE OR IN PART) WITHOUT PROPER AUTHORIZATION OF U.S.F. FABRICATION, INC.

INTERPRET DIMENSIONS AND TOLERANCES PER ASME Y14.5M

BREAK ALL SHARP CORNERS & EDGES TO 0.01

TOLERANCES UNLESS OTHERWISE SPECIFIED FRACTIONAL

INCHES = $\pm 1/16$
 $1/16 = \pm 1/32$
 $1/32 = \pm 1/64$

COPYRIGHT © 2020
 ALL RIGHTS RESERVED

MOD. "E" INLET TRAFFIC



U.S.F. FABRICATION INC.
 HIALEAH, FLORIDA

GRATE RVT 6695 H20 PTD

DWN. BY:	ALJ	SCALE:	1"=12"	SHEET:	1 of 1	DATE:	7/30/15
CHK. BY:	ALJ	DWG.#	100001551	SHEET SIZE:	B	REV:	5