



**NOTES**

1. MATL: STEEL A36, HOT DIP GALVANIZED AFTER FABRICATION
2. DESIGNED FOR AASHTO H20 WHEEL LOADS WITH MAX DEFL OF 1/150 OF THE SPAN
3. APPROXIMATE WEIGHT: 157.39 lbs.
4. APPROXIMATE WEIGHT WITH GALVANIZING: 166.83 lbs.

TYPE 24-10S

| REV. | DATE     | BY   | CHK. | DESCRIPTION                              |
|------|----------|------|------|--|
| 2    | 04/22/21 | A.Q. | A.Q. | WELDING CALLOUTS UP DATED PER ECO#21-066 |
| 1    | 03/25/21 | A.Q. | A.Q. | REDUCED NOTCH FROM 2 3/4 TO 2 1/2"       |

THIS DOCUMENT IS THE PROPERTY OF U.S.F. FABRICATION, INC AND CONTAINS PROPRIETARY INFORMATION. IT SHALL NOT BE MODIFIED, COPIED, FURNISHED NOR DISTRIBUTED (IN WHOLE OR IN PART) WITHOUT PROPER AUTHORIZATION OF U.S.F. FABRICATION, INC.

INTERPRET DIMENSIONS AND TOLERANCES PER ASME Y14.5M

BREAK ALL SHARP CORNERS & EDGES TO 0.01

TOLERANCES UNLESS OTHERWISE SPECIFIED FRACTIONAL

INCHES = ± 1/16  
1/16 = ± 1/32  
1/32 = ± 1/64

COPYRIGHT © 2018  
ALL RIGHTS RESERVED



**U.S.F. FABRICATION INC.**  
HIALEAH, FLORIDA

RIVETED STEEL GRATING-40 X 23 5/8 (OVERALL) X 3 1/2

|                     |                     |                  |                   |
|---------------------|---------------------|------------------|-------------------|
| DWN. BY:<br>USFFWIZ | SCALE:<br>1:16      | SHEET:<br>1 of 1 | DATE:<br>11/01/18 |
| CHK. BY:<br>JM      | DWG.#<br>1000027266 | SHEET<br>SIZE: B | REV:<br>2         |