



**NOTES:**

- 1- MATERIAL: STEEL A36, HOT DIP GALVANIZED AFTER FABRICATION IN ACCORDANCE WITH ASTM A-123
- △ 2- LOADING: H-25 WHEEL LOADS
- 3- APPROXIMATE WEIGHT: 100 LBS.

REV.	DATE	BY	CHK.	DESCRIPTION
2	2/18/19	DAV	DAV	ADDED H-25 LOADING NOTE.
1	10/23/18	DAV	DAV	UPDATED DWG FORMAT. 54 1/8 WAS 54. ADDED HOLE.

THIS DOCUMENT IS THE PROPERTY OF U.S.F. FABRICATION, INC AND CONTAINS PROPRIETARY INFORMATION. IT SHALL NOT BE MODIFIED, COPIED, FURNISHED NOR DISTRIBUTED (IN WHOLE OR IN PART) WITHOUT PROPER AUTHORIZATION OF U.S.F. FABRICATION, INC.

INTERPRET DIMENSIONS AND TOLERANCES PER ASME Y14.5M

BREAK ALL SHARP CORNERS & EDGES TO 0.01

**TOLERANCES UNLESS OTHERWISE SPECIFIED:**

INCHES =  $\pm 1/16$   
 1/16 =  $\pm 1/32$   
 1/32 =  $\pm 1/64$

COPYRIGHT © 2018  
 ALL RIGHTS RESERVED

MARYLAND DEPT. OF TRANSPORTATION



**U.S.F. FABRICATION INC.**  
 HIALEAH, FLORIDA

**SUPPORT BEAM WITH ANGLES  
 STEEL**

DRAWN BY: D.B.	SCALE: 1=8	SHEET: 1 OF 1	DATE: 2/24/05
APP'D BY: D.B.	DWG. NO: 1000083898	SHEET SIZE: B	REV: 2