



1/4  $\phi$  HOLE TO FACILITATE GALVANIZING PROCESS

- NOTES:**
- 1- MATERIAL: STEEL A36, HOT DIP GALVANIZED AFTER FABRICATION IN ACCORDANCE WITH ASTM A-123
  - 2- APPROXIMATE WEIGHT: 174 LBS.
  - 3- LOADING: H-25 WHEEL LOADS.

THIS DOCUMENT IS THE PROPERTY OF U.S.F. FABRICATION, INC AND CONTAINS PROPRIETARY INFORMATION. IT SHALL NOT BE MODIFIED, COPIED, FURNISHED NOR DISTRIBUTED (IN WHOLE OR IN PART) WITHOUT PROPER AUTHORIZATION OF U.S.F. FABRICATION, INC.

INTERPRET DIMENSIONS AND TOLERANCES PER ASME Y14.5M  
 BREAK ALL SHARP CORNERS & EDGES  
**TOLERANCES UNLESS OTHERWISE SPECIFIED:**  
 INCHES AND FRACTIONS:  
 <10' =  $\pm$  1/8  
 >10' =  $\pm$  1/4

COPYRIGHT © 2022 ALL RIGHTS RESERVED

STANDARD No. MD-374.13 – INLET TYPE NRM			
<b>MARYLAND DEPARTMENT OF TRANSPORTATION</b>			
<b>U.S.F. FABRICATION INC.</b> HIALEAH, FLORIDA			
<b>SUPPORT BEAM STEEL GALVANIZED</b>			
DRAWN BY:	SCALE:	SHEET:	DATE:
TA/ALJ	1=8	1 of 1	04/14/22
APP'D BY:	DWG. NO.:	SHEET SIZE:	REV:
TA/ALJ	1000130371	B	0