



- NOTES:**
- 1-FRAME TO BE SQUARE, FLAT AND TRUE.
  - 2-STRUCTURAL STEEL SHALL BE A.S.T.M. A-36
  - 3-FRAME TO BE GALVANIZED AFTER FABRICATION IN ACCORDANCE WITH A.S.T.M. A-123.
  - 4-APPROXIMATE WEIGHT AFTER GALVANIZED: 333 LBS.
  - 5-FOR GRATES DETAILS SEE ITEM 1000110220.

THIS DOCUMENT IS THE PROPERTY OF U.S.F. FABRICATION, INC AND CONTAINS PROPRIETARY INFORMATION. IT SHALL NOT BE MODIFIED, COPIED, FURNISHED NOR DISTRIBUTED (IN WHOLE OR IN PART) WITHOUT PROPER AUTHORIZATION OF U.S.F. FABRICATION, INC.

INTERPRET DIMENSIONS AND TOLERANCES PER ASME Y14.5M
BREAK ALL SHARP CORNERS & EDGES
<b>TOLERANCES UNLESS OTHERWISE SPECIFIED:</b>
INCHES AND FRACTIONS:
< 10' = ± 1/8
> 10' = ± 1/4

COPYRIGHT © 2020  
ALL RIGHTS RESERVED

MARYLAND DEPARTMENT OF TRANSPORTATION



STANDARD DOUBLE FRAME, STEEL MODIFIED

DRAWN BY: A.Q.	SCALE: 1:20	SHEET: 1 OF 1	DATE: 07/27/20
APP'D BY: A.Q.	DWG. NO: 1000160229	SHEET SIZE: B	REV: 0