



1/4 ϕ HOLE TO FACILITATE GALVANIZING PROCESS

NOTES:

- 1- MATERIAL: STEEL A36, HOT DIP GALVANIZED AFTER FABRICATION IN ACCORDANCE WITH ASTM A-123
- 2- APPROXIMATE WEIGHT: 230 LBS.
- 3- LOADING: H-25 WHEEL LOADS.

THIS DOCUMENT IS THE PROPERTY OF U.S.F. FABRICATION, INC AND CONTAINS PROPRIETARY INFORMATION. IT SHALL NOT BE MODIFIED, COPIED, FURNISHED NOR DISTRIBUTED (IN WHOLE OR IN PART) WITHOUT PROPER AUTHORIZATION OF U.S.F. FABRICATION, INC.

INTERPRET DIMENSIONS AND TOLERANCES PER ASME Y14.5M

BREAK ALL SHARP CORNERS & EDGES

TOLERANCES UNLESS OTHERWISE SPECIFIED:
INCHES AND FRACTIONS:

<10' = $\pm 1/8$
>10' = $\pm 1/4$

COPYRIGHT © 2020 ALL RIGHTS RESERVED

STANDARD No. MD-374.03 – INLET TYPE WRM

MARYLAND DEPARTMENT OF TRANSPORTATION



U.S.F. FABRICATION INC.
HIALEAH, FLORIDA

SUPPORT BEAM
STEEL GALVANIZED

DRAWN BY: A.Q.	SCALE: 1:8	SHEET: 1 of 1	DATE: 07/29/20
APP'D BY: A.Q.	DWG. NO.: 1000160300	SHEET SIZE: B	REV: 0